




www.hrltyres.com

HANDAS RUBBERS PRIVATE LIMITED

Manufactured Unit:- Opp Industrial Area, New Rohtak Road,
Bye Pass Sonipat-131001. Haryana. (India)

 www.hrltyres.com



Government of India
Ministry of Commerce and Industry
Directorate General of Foreign Trade
Office of the Additional Director General of Foreign Trade, CLA Delhi
Central Licensing Area (CLA), A Wing I.P. Bhawan, I.P. Estate, New Delhi

Importer-Exporter Code

This is to certify that **HANDAS RUBBERS PRIVATE LIMITED** is issued an
Importer-Exporter Code (IEC) 0508069238 with details as follows -

IEC	0508069238
PAN	AAACH0081M
Firm Name	HANDAS RUBBERS PRIVATE LIMITED
Nature of Concern	Private Limited
Date of Issue	07/01/2009
Registered Address	418/35, 1ST FLOOR, NEW ESPLANADE, ROAD Contact No., NEW DELHI, NORTH DELHI, DELHI, 110006
Name of the Signatory	PRAMOD CHHIKARA
Director / Partner Details	Refer online at https://dgft.gov.in or scan the QR Code
Branch Details	Refer online at https://dgft.gov.in or scan the QR Code

Last Modified : 13/06/2022
File Number : DLIECPAMEND00025715AM23



Note : This is a system-generated certificate. Authenticity / Updated details of the IEC can be checked at official DGFT website <https://dgft.gov.in> by entering the IEC and Firm Name under Services > View Any IEC Details. You can also authenticate the certificate by scanning the QR code.



CERTIFICATE

This is to certify that the
QUALITY MANAGEMENT SYSTEMS
of

HANDAS RUBBERS PVT. LTD.
Bye Pass Rohtak Road, Opp. Industrial Area,
Sonepat- 131001, Haryana, India

has been assessed and found to be in conformance to the requirements of

ISO 9001:2015

This certificate is valid for the following activity:

Manufacturing of Auto Rickshaw Tyre,
E Rickshaw Tyre, Cycle Tyre & Rickshaw Tyre

Certificate No.: IQ-22082401

Date of initial Registration: 25-08-2020
Date of this Certificate: 24-08-2024
Certificate Expiry: 24-08-2025*
Recertification Due: 24-08-2026

S. Chikara
Auth Sign

*Registration is subject to the system being continually maintained to the above standard under regular surveillance.
To check the certification validity please visit- <https://www.lafcertsearch.org/> or www.ispcert.com



Indraprastha SystemCert Pvt. Ltd.

Accredited by EGAC, A Member of International Accreditation Forum
For updated information of Certification, visit- www.ispcert.com, or E Mail- info@ispcert.com
201, Jaina Tower-3, A-1, Janak Puri, New Delhi-110058, India. Ph-+91 9980 477 631



1/25/2021

Print : Udyam Registration Certificate

भारत सरकार
Government of India
सूक्ष्म, लघु एवं मध्यम उद्यम मंत्रालय
Ministry of Micro, Small and Medium Enterprises

UDYAM
REGISTRATION CERTIFICATE

Our small hands to make you LARGE

TYPE OF ENTERPRISE	SMALL	MANUFACTURING																				
UDYAM REGISTRATION NUMBER	UDYAM-DL-01-0004378																					
NAME OF ENTERPRISE	MS HANDAS RUBBERS PRIVATE LIMITED																					
SOCIAL CATEGORY OF ENTREPRENEUR	General																					
NAME OF UNITS	<table border="1"> <tr> <th>SNo.</th> <th>Udyog Authar Memorandum</th> <th>Unit Name</th> </tr> <tr> <td>1</td> <td>DLERA009478</td> <td>HANDAS RUBBERS PRIVATE LIMITED</td> </tr> </table>		SNo.	Udyog Authar Memorandum	Unit Name	1	DLERA009478	HANDAS RUBBERS PRIVATE LIMITED														
SNo.	Udyog Authar Memorandum	Unit Name																				
1	DLERA009478	HANDAS RUBBERS PRIVATE LIMITED																				
OFFICAL ADDRESS OF ENTERPRISE	<table border="1"> <tr> <th>Plot/Block No.</th> <td>418/35</td> <th>Name of Premises/Building</th> <td>1ST FLR NEW</td> </tr> <tr> <th>Village/Town</th> <td>DELHI</td> <th>Block</th> <td>1ST FLR</td> </tr> <tr> <th>Road/Street/Lane</th> <td>ESPLANDE RD</td> <th>City</th> <td>DELHI</td> </tr> <tr> <th>State</th> <td>DELHI</td> <th>District</th> <td>CENTRAL, Pin 110006</td> </tr> <tr> <th>Mobile</th> <td>9812228027</td> <th>Email:</th> <td>hrj22009@yahoo.com</td> </tr> </table>		Plot/Block No.	418/35	Name of Premises/Building	1ST FLR NEW	Village/Town	DELHI	Block	1ST FLR	Road/Street/Lane	ESPLANDE RD	City	DELHI	State	DELHI	District	CENTRAL, Pin 110006	Mobile	9812228027	Email:	hrj22009@yahoo.com
Plot/Block No.	418/35	Name of Premises/Building	1ST FLR NEW																			
Village/Town	DELHI	Block	1ST FLR																			
Road/Street/Lane	ESPLANDE RD	City	DELHI																			
State	DELHI	District	CENTRAL, Pin 110006																			
Mobile	9812228027	Email:	hrj22009@yahoo.com																			
DATE OF INCORPORATION / REGISTRATION OF ENTERPRISE	20/10/1992																					
DATE OF COMMENCEMENT OF PRODUCTION/BUSINESS	20/10/1992																					
NATIONAL INDUSTRY CLASSIFICATION CODE(S)	<table border="1"> <tr> <th>SNo.</th> <th>NIC 3 Digit</th> <th>NIC 4 Digit</th> <th>NIC 5 Digit</th> <th>Activity</th> </tr> <tr> <td>1</td> <td>22</td> <td>2211</td> <td>22119</td> <td>Manufacture of rubber and plastics products</td> </tr> <tr> <td></td> <td></td> <td>2211</td> <td>22119</td> <td>Manufacture of rubber tyres and tubes, retreading and rebuilding of rubber tyres</td> </tr> <tr> <td></td> <td></td> <td>2211</td> <td>22119</td> <td>Manufacture of rubber tyres and tubes n.e.c.</td> </tr> </table>		SNo.	NIC 3 Digit	NIC 4 Digit	NIC 5 Digit	Activity	1	22	2211	22119	Manufacture of rubber and plastics products			2211	22119	Manufacture of rubber tyres and tubes, retreading and rebuilding of rubber tyres			2211	22119	Manufacture of rubber tyres and tubes n.e.c.
SNo.	NIC 3 Digit	NIC 4 Digit	NIC 5 Digit	Activity																		
1	22	2211	22119	Manufacture of rubber and plastics products																		
		2211	22119	Manufacture of rubber tyres and tubes, retreading and rebuilding of rubber tyres																		
		2211	22119	Manufacture of rubber tyres and tubes n.e.c.																		
DATE OF UDYAM REGISTRATION	25/01/2021																					

Disclaimer: This is computer generated statement, no signature required.
Printed from <https://udyamregistration.gov.in>

For any assistance, you may contact:

- DIC DELHI
- MSME-DI DELHI



FEDERATION OF INDIAN EXPORT ORGANISATIONS
FIEO Northern Region - New Delhi
Niryat Bhawan Rao Tula Ram Marg, Opp. Army Hospital Research & Referral, New Delhi,
NEW DELHI, DELHI, 110057.
Email - fieo@fieo.org, Telephone - 011-4604222 Website - <https://www.fieo.org>

REGISTRATION CUM MEMBERSHIP CERTIFICATE
(Issued under the provisions of Foreign Trade Policy, Government of India)

Name of the exporter	HANDAS RUBBERS PRIVATE LIMITED
IEC Number	0508069238
Address of the Registered/Head Office	418/35, 1ST FLOOR, NEW ESPLANADE ROAD Contact No., NEW DELHI, 110006, NORTH DELHI, DELHI
Nature of Concern	Private Limited
Description of goods/ services for which registered	AUTO TYRE AND AGRICULTURE TYRE
Registration Number	NR/982/2020-2021
Issued against File Number	RCMCRNWFIEO0006316AM24
Registered as	Merchant Cum Manufacturer Exporter
Name of the Proprietor/ Partner(s)/Director(s)/Karta	Venka Chikara/Baldev Singh Chikara/Pramod Chikara

This certificate is issued as per the details of our records and is subject to the conditions laid down in the relevant scheme of registration of this council.

Issue Date: 18/01/2024
Renew upto: 31/03/2026

Signature Not Verified
Digitally signed by MUKESH KUMAR, DN: cn=MUKESH KUMAR, o=Indraprastha SystemCert Pvt. Ltd., email=MUKESH.KUMAR@ispcert.com, c=IN, 1.3.6.1.5.5-2.1.1=EGAC, 1.3.6.1.5.5-2.1.2=ISPL, 1.3.6.1.5.5-2.1.3=IAF, 1.3.6.1.5.5-2.1.4=IAAF, 1.3.6.1.5.5-2.1.5=IAFAC, 1.3.6.1.5.5-2.1.6=IAFAC, 1.3.6.1.5.5-2.1.7=IAFAC, 1.3.6.1.5.5-2.1.8=IAFAC, 1.3.6.1.5.5-2.1.9=IAFAC, 1.3.6.1.5.5-2.1.10=IAFAC, 1.3.6.1.5.5-2.1.11=IAFAC, 1.3.6.1.5.5-2.1.12=IAFAC, 1.3.6.1.5.5-2.1.13=IAFAC, 1.3.6.1.5.5-2.1.14=IAFAC, 1.3.6.1.5.5-2.1.15=IAFAC, 1.3.6.1.5.5-2.1.16=IAFAC, 1.3.6.1.5.5-2.1.17=IAFAC, 1.3.6.1.5.5-2.1.18=IAFAC, 1.3.6.1.5.5-2.1.19=IAFAC, 1.3.6.1.5.5-2.1.20=IAFAC, 1.3.6.1.5.5-2.1.21=IAFAC, 1.3.6.1.5.5-2.1.22=IAFAC, 1.3.6.1.5.5-2.1.23=IAFAC, 1.3.6.1.5.5-2.1.24=IAFAC, 1.3.6.1.5.5-2.1.25=IAFAC, 1.3.6.1.5.5-2.1.26=IAFAC, 1.3.6.1.5.5-2.1.27=IAFAC, 1.3.6.1.5.5-2.1.28=IAFAC, 1.3.6.1.5.5-2.1.29=IAFAC, 1.3.6.1.5.5-2.1.30=IAFAC, 1.3.6.1.5.5-2.1.31=IAFAC, 1.3.6.1.5.5-2.1.32=IAFAC, 1.3.6.1.5.5-2.1.33=IAFAC, 1.3.6.1.5.5-2.1.34=IAFAC, 1.3.6.1.5.5-2.1.35=IAFAC, 1.3.6.1.5.5-2.1.36=IAFAC, 1.3.6.1.5.5-2.1.37=IAFAC, 1.3.6.1.5.5-2.1.38=IAFAC, 1.3.6.1.5.5-2.1.39=IAFAC, 1.3.6.1.5.5-2.1.40=IAFAC, 1.3.6.1.5.5-2.1.41=IAFAC, 1.3.6.1.5.5-2.1.42=IAFAC, 1.3.6.1.5.5-2.1.43=IAFAC, 1.3.6.1.5.5-2.1.44=IAFAC, 1.3.6.1.5.5-2.1.45=IAFAC, 1.3.6.1.5.5-2.1.46=IAFAC, 1.3.6.1.5.5-2.1.47=IAFAC, 1.3.6.1.5.5-2.1.48=IAFAC, 1.3.6.1.5.5-2.1.49=IAFAC, 1.3.6.1.5.5-2.1.50=IAFAC, 1.3.6.1.5.5-2.1.51=IAFAC, 1.3.6.1.5.5-2.1.52=IAFAC, 1.3.6.1.5.5-2.1.53=IAFAC, 1.3.6.1.5.5-2.1.54=IAFAC, 1.3.6.1.5.5-2.1.55=IAFAC, 1.3.6.1.5.5-2.1.56=IAFAC, 1.3.6.1.5.5-2.1.57=IAFAC, 1.3.6.1.5.5-2.1.58=IAFAC, 1.3.6.1.5.5-2.1.59=IAFAC, 1.3.6.1.5.5-2.1.60=IAFAC, 1.3.6.1.5.5-2.1.61=IAFAC, 1.3.6.1.5.5-2.1.62=IAFAC, 1.3.6.1.5.5-2.1.63=IAFAC, 1.3.6.1.5.5-2.1.64=IAFAC, 1.3.6.1.5.5-2.1.65=IAFAC, 1.3.6.1.5.5-2.1.66=IAFAC, 1.3.6.1.5.5-2.1.67=IAFAC, 1.3.6.1.5.5-2.1.68=IAFAC, 1.3.6.1.5.5-2.1.69=IAFAC, 1.3.6.1.5.5-2.1.70=IAFAC, 1.3.6.1.5.5-2.1.71=IAFAC, 1.3.6.1.5.5-2.1.72=IAFAC, 1.3.6.1.5.5-2.1.73=IAFAC, 1.3.6.1.5.5-2.1.74=IAFAC, 1.3.6.1.5.5-2.1.75=IAFAC, 1.3.6.1.5.5-2.1.76=IAFAC, 1.3.6.1.5.5-2.1.77=IAFAC, 1.3.6.1.5.5-2.1.78=IAFAC, 1.3.6.1.5.5-2.1.79=IAFAC, 1.3.6.1.5.5-2.1.80=IAFAC, 1.3.6.1.5.5-2.1.81=IAFAC, 1.3.6.1.5.5-2.1.82=IAFAC, 1.3.6.1.5.5-2.1.83=IAFAC, 1.3.6.1.5.5-2.1.84=IAFAC, 1.3.6.1.5.5-2.1.85=IAFAC, 1.3.6.1.5.5-2.1.86=IAFAC, 1.3.6.1.5.5-2.1.87=IAFAC, 1.3.6.1.5.5-2.1.88=IAFAC, 1.3.6.1.5.5-2.1.89=IAFAC, 1.3.6.1.5.5-2.1.90=IAFAC, 1.3.6.1.5.5-2.1.91=IAFAC, 1.3.6.1.5.5-2.1.92=IAFAC, 1.3.6.1.5.5-2.1.93=IAFAC, 1.3.6.1.5.5-2.1.94=IAFAC, 1.3.6.1.5.5-2.1.95=IAFAC, 1.3.6.1.5.5-2.1.96=IAFAC, 1.3.6.1.5.5-2.1.97=IAFAC, 1.3.6.1.5.5-2.1.98=IAFAC, 1.3.6.1.5.5-2.1.99=IAFAC, 1.3.6.1.5.5-2.1.100=IAFAC

Tractor Front Tires (F-2) Double Rib





Specially profiled central rib for deeper penetration and steering control

Adequately reinforced rib base for minimum lateral side-slipping.

Strong and Sturdy body plies for longer service durability.

Cut sand Cracks resistant tread compound for increased service life



SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch														
6.00-16	F 2	8	4.5	TT	165	6.49	735	28.93	13	16	670	1474	4.6	65	94	A8/40kmph	A8/25mph
7.50-16	F 2	8	5.5	TT	205	8.0	807.7	31.8	14	18	875	1925	3.8	54	103	A8/40kmph	A8/25mph

Tractor Front Tires (F-2) Double Rib





Specially profiled central rib for deeper penetration and steering control

Adequately reinforced rib base for minimum lateral side-slipping.

Strong and Sturdy body plies for longer service durability.

Cut sand Cracks resistant tread compound for increased service life



SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch														
6.00-16	F 2	8	4.5	TT	165	6.49	735	28.93	13	16	670	1474	4.6	65	94	A8/40kmph	A8/25mph
7.50-16	F 2	8	5.5	TT	205	8.0	807.7	31.8	14	18	875	1925	3.8	54	103	A8/40kmph	A8/25mph





Tractor Front Tires (F-2) Single Rib

On and off road type for 2WD tractor.

Ensures better steering control on fields.

Extra deep tread.







SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch														
6.00-16	F 2	8	4.5	TT	165	6.49	735	28.93	13	16	670	1474	4.6	65	94	A8/40kmph	A8/25mph
7.50-16	F 2	8	5.5	TT	205	8.0	807.7	31.8	14	18	875	1925	3.8	54	103	A8/40kmph	A8/25mph

Tractor Front Tires (F-2) Three Rib

- ◆ Penetrates deep into soil for maximum steering control and minimal lateral side-slip because of its high center rib.
- ◆ Best for handling heavy loads on hard-packed surfaces.







SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch														
6.00-16	F 2	8	4.5	TT	165	6.49	735	28.93	13	16	670	1474	4.6	65	94	A8/40kmph	A8/25mph
7.50-16	F 2	8	5.5	TT	205	8.0	807.7	31.8	14	18	875	1925	3.8	54	103	A8/40kmph	A8/25mph

Tractor Front Tires (F-2) Double Rib

- ◆ Specially profiled central rib for deeper penetration and steering control
- ◆ Adequately reinforced rib base for minimum lateral side-slipping.
- ◆ Strong and Sturdy body plies for longer service durability.
- ◆ Cuts and Cracks resistant tread compound for increased service life







SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYPE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	Mph
			inch														
9.00-16	F 2	10	7.0	TT	234	9.2	854	33.6	15	19	1260	2750	3.9	55	116	A8/40kmph	A8/25 mph
10.00-16	F 2	10	7.0	TT	275	10.8	900	35.4	18		1360	2992	2.9	41	119	A8/40kmph	A8/25 mph

Farm implement & farm service (I-1)

- ◆ Heavier load capacity ensures the tire to operate under severe working conditions by providing excellent performance.
- ◆ It is suitable for agriculture implement and trailer use, both On-Road & Off-Road



SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYPE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	Mph
			inch														
11L-15	I-1	8	8.0	TL	270	10.6	790	31.1	8	10	1150	2530	2.5	35	113	D/65 kmph	D/40mph
11L-15	I-1	12	8.0	TL	270	10.6	790	31.1	8	10	1450	3190	3.6	51	121	D/65 kmph	D/40mph
11L-16	I-1	8	8.0	TL	270	10.6	795	31.3	8	10	1215	2992	2.5	36	130	D/65 kmph	D/40mph
12.5L-16SL	I-1	12	10.0	TL	310	12.2	845	33.2	8	10	1800	3960	3.7	52	130	D/65 kmph	D/40mph
12.5L-16SL	I-1	14	10.0	TL	310	12.2	845	33.2	8	10	2000	4400	3.9	55	132	D/65 kmph	D/40mph

Tractor Trailer Tires

- ◆ Longitudinal, evenly spaced ribs for required free rolling characteristics.
- ◆ Suitably profiled shoulder region with lateral grooves to control slide slips.
- ◆ Strong and heavy duty NYLON body plies for higher load carrying capacity
- ◆ Tread compound for longer service life during all weather conditions



SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED		
					inch		mm	inch	mm	inch	mm	32nds	kg	lbs		bar	psi	kmph
			mm		inch	mm												
9.00-16	SAND/LUG	8	6.5	TT	244	9.6	905	35.5	25	30	1375	3025	3.4	49	119	G/90kmph	B/56mph	
9.00-16	SANLUG	14	6.5	TT	244	9.6	905	35.5	25	30	1650	3630	6.3	89	125	G/90kmph	B/56mph	

Tractor Trailer Tires

- ◆ Longitudinal, evenly spaced ribs for required free rolling characteristics.
- ◆ Suitably profiled shoulder region with lateral grooves to control slide slips.
- ◆ Strong and heavy duty NYLON body plies for higher load carrying capacity
- ◆ Tread compound for longer service life during all weather conditions



SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED		
					inch		mm	inch	mm	inch	mm	32nds	kg	lbs		bar	psi	kmph
			mm		inch	mm												
9.00-16	LUG	8	6.5	TT	244	9.6	905	35.5	25	30	1375	3025	3.4	49	119	G/90kmph	B/56mph	
9.00-16	LUG	14	6.5	TT	244	9.6	905	35.5	25	30	1650	3630	6.3	89	125	G/90kmph	B/56mph	

Tractor Trailer Tires

- ◆ Longitudinal, evenly spaced ribs for required free rolling characteristics.
- ◆ Suitably profiled shoulder region with lateral grooves to control slide slips.
- ◆ Strong and heavy duty NYLON body plies for higher load carrying capacity
- ◆ Tread compound for longer service life during all weather conditions



SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED		
					inch		mm	inch	mm	inch	mm	32nds	kg	lbs		bar	psi	kmph
			mm		inch	mm												
9.00-16	LUG	8	6.5	TT	244	9.6	905	35.5	23	28	1375	3025	3.4	49	119	G/90kmph	B/56 mph	
9.00-16	LUG	14	6.5	TT	244	9.6	905	35.5	23	28	1650	3630	6.3	89	125	G/90kmph	B/56 mph	

Tractor Trailer Tires

- ◆ Longitudinal, evenly spaced ribs for required free rolling characteristics.
- ◆ Suitably profiled shoulder region with lateral grooves to control slide slips.
- ◆ Strong and heavy duty NYLON body plies for higher load carrying capacity
- ◆ Tread compound for longer service life during all weather conditions



SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			inch		mm		mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
					mm	inch											
7.00-16	MILITARY	8	5.5	TT	196	7.7	785	3.9	12	15	975	2145	3.8	40	107	G/90kmph	B/56mph
7.50-16	MILITARY	8	6.0	TT	221	8.7	825	32.5	12	15	1080	2376	4.2	61	111	G/90kmph	B/56mph
7.50-16	MILITARY	10	6.0	TT	221	8.7	825	32.5	12	15	1250	2750	6.2	89	116	G/90kmph	B/56mph

Agriculture and Trailer Implement Tires

- ◆ Multirib and low section tire designed for high flotation.
- ◆ Optimised rib width and profiled shoulder for on and off the road service
- ◆ Extra reinforced plies for higher load capacity of farm implement.
- ◆ Cuts and cracks resistant tread compound for extra service life.




SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			inch		mm		mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
					mm	inch											
10.0/80-12	AW	8	9.0	TL	264	10.4	710	28	8	9	1250	2750	4.2	60	116	A8/40kmph	A8/25 mph
10.0/80-12	AW	10	9.0	TL	264	10.4	710	28	8	9	1420	3124	5.4	77	121	A8/40kmph	A8/25 mph
10.0/75-15.3	AW	10	9.0	TL	264	10.5	760	29.9	8	10	1550	3410	5.2	74	123	A8/40kmph	A8/25 mph
10.0/75-15.3	AW	12	9.0	TL	264	10.5	760	29.9	8	10	1700	3750	6.4	91	126	A8/40kmph	A8/25 mph
10.0/75-15.3	AW	14	9.0	TL	264	10.5	760	29.9	8	10	1900	4180	7.1	101	130	A8/40kmph	A8/25 mph
10.0/75-15.3	AW	18	9.0	TL	264	10.5	760	29.9	8	10	2360	5192	7.1	101	138	A8/40kmph	A8/25 mph
10.0/75-15.3	AW	22	9.0	TL	264	10.5	760	29.9	8	10	2750	6050	7.5	108	143	A8/40kmph	A8/25 mph
10.5/65-16	AW	10	9.0	TL	274	10.78	755	29.7	8	10	1550	3410	5.3	75	123	A8/40kmph	A8/25 mph
10.5/65-16	AW	14	9.0	TL	274	10.78	755	29.7	8	10	1900	4180	7.3	104	130	A8/40kmph	A8/25 mph
11.5/80-15.3	AW	10	9.0	TL	290	11.4	845	33.8	9	11	1050	4300	4.6	65	131	A8/40kmph	A8/25 mph
11.5/80-15.3	AW	12	9.0	TL	290	11.4	845	33.8	9	11	2180	4800	5.6	79	135	A8/40kmph	A8/25 mph
11.5/80-15.3	AW	14	9.0	TL	290	11.4	845	33.8	9	11	2430	5346	6.5	92	139	A8/40kmph	A8/25 mph
11.5/80-15.3	AW	16	9.0	TL	290	11.4	845	33.8	9	11	2575	5675	7.1	101	141	A8/40kmph	A8/25 mph
11.5/80-15.3	AW	18	9.0	TL	290	11.4	845	33.8	9	11	2900	6375	7.8	111	145	A8/40kmph	A8/25 mph
11.5/80-15.3	AW	22	9.0	TL	290	11.4	845	33.8	9	11	3250	7150	7.9	112	149	A8/40kmph	A8/25 mph

All Terrain traction Tires (R-1)

- ◆ Multi Angles curved log bars specially designed to get excellent traction or wet and sticky oil with Excellent self-cleaning properties, preventing mud clogging between the lugs.
- ◆ Sidewall rubber preventing weather cracking.
- ◆ Tough tread compound to resist fast wear.




SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch														
4.00-8	R1	4	3.0	TT	114	4.4	425	16.7	10	13	170	374	1.6	23	46	A8/40kmph	A8/25mph
5.00-12	R1	6	4.0	TT	145	5.7	580	22.8	13	16	425	935	3.2	54	78	A8/40kmph	A8/25mph
6.00-12	R1	6	4.0	TT	153	6.0	585	23.0	16	20	345	759	2.5	36	71	A8/40kmph	A8/25mph
7.00-12	R1	8	6.0	TT	187	7.4	683	26.8	16	20	487	1071	2.5	53	88	A8/40kmph	A8/25mph
6.00-16	R1	8	4.5	TT	170	6.6	745	29.3	16	20	545	1199	4.5	41	83	A8/40kmph	A8/25mph

All Terrain traction Tires (R-1)

- ◆ Multi Angles curved log bars specially designed to get excellent traction or wet and sticky oil with Excellent self-cleaning properties, preventing mud clogging between the lugs.
- ◆ Sidewall rubber preventing weather cracking.
- ◆ Tough tread compound to resist fast wear.







SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch														
6.5/80-12	R1	6	5.0	TT/TL	165	6.5	590	23.2	16	20	710	1562	3.7	53	96	A8/40kmph	A8/25mph
6.5/80-13	R1	6	5.0	TT/TL	170	6.7	640	25.1	16	20	930	2046	3.1	44	105	A8/40kmph	A8/25mph
6.5/80-15	R1	8	5.0	TT/TL	163	6.4	663	26.1	15	19	950	2090	3.6	52	100	A8/40kmph	A8/25mph
6.-14	R1	4	5.0	TT	157	6.1	655	26.0	25	31	300	660	2.0	28	66	A8/40kmph	A8/25mph
7.-14	R1	4	6.0	TT	180	7.0	691	27.2	25	31	375	825	2.0	28	74	A8/40kmph	A8/25mph

Tractor Rear Drive Wheel Tires (R-1)

- ◆ Specially designed for traction, these tires with deep treads, provides excellent traction for general farming.
- ◆ Self-cleaning deep lugs are especially designed to provide high traction and long life under hard working condition, including On-Road service.



SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch														
8.3-24	R1	6	7.0	TT	211	8.3	993	39.1	26	33	800.0	1760	2.4	35	100	A6/30kmph	A6/20mph
8.3-24	R1	8	7.0	TT	211	8.3	993	39.1	26	33	925.0	2035	3.1	45	105	A6/30kmph	A6/20mph
9.5-24	R1	8	7.0	TT	241	9.4	1050	41.3	26	33	1120	2464	2.9	41	112	A6/30kmph	A6/20mph
11.2-24	R1	8	10.0	TT	284	11.2	1105	43.5	28	35	1250	2750	2.5	36	116	A6/30kmph	A6/20 mph
12.4-24	R1	8	11.0	TT	315	12.4	1165	45.9	29	36	1450	3190	2.3	33	121	A6/30kmph	A6/20 mph
12.4-24	R1	12	11.0	TT	315	12.4	1165	45.9	29	36	1800	3960	3.6	51	128	A6/30kmph	A6/20 mph
12.4-28	R1	8	11.0	TT	315	12.4	1260	49.6	32	40	1550	3410	2.3	33	123	A6/30kmph	A6/20 mph
12.4-28	R1	12	11.0	TT	315	12.4	1260	49.6	32	40	1990	4378	3.1	44	130	A6/30kmph	A6/20 mph
13.6-28	R1	8	12.0	TT	345	13.6	1310	51.6	36	45	1650	3630	2.0	28	125	A6/30kmph	A6/20 mph
13.6-28	R1	12	12.0	TT	345	13.6	1310	51.6	36	45	2075	4565	2.4	34	133	A6/30kmph	A6/20 mph
14.9-28	R1	8	13.0	TT	378	14.9	1365	53.7	33	41	1900	4180	1.8	26	130	A6/30kmph	A6/20 mph
14.9-28	R1	12	13.0	TT	378	14.9	1365	53.7	33	41	2300	5060	2.6	37	137	A6/30kmph	A6/20 mph
16.9-28	R1	8	15.0	TT	429	16.9	1435	56.5	35	48	2180	4796	1.8	26	130	A6/30kmph	A6/20 mph
16.9-28	R1	12	15.0	TT	429	16.9	1435	56.5	35	48	2725	5995	2.4	34	143	A6/30kmph	A6/20 mph
16.9-30	R1	8	15.0	TT	429	16.9	1485	58.5	36	45	2300	5060	1.8	26	137	A6/30kmph	A6/20 mph
16.9-30	R1	12	15.0	TT	429	16.9	1485	58.5	36	45	2725	5995	2.5	36	143	A6/30kmph	A6/20 mph
18.4-30	R1	10	16.0	TT	467	18.4	1550	61.0	38	48	2650	5830	1.6	23	142	A6/30kmph	A6/20 mph
18.4-30	R1	14	16.0	TT	467	18.4	1550	61.0	38	48	3450	7590	2.7	39	151	A6/30kmph	A6/20 mph
18.4-34	R1	8	16.0	TT	467	18.4	1660	65.3	38	48	2650	5830	1.4	26	139	A6/30kmph	A6/20 mph
18.4-34	R1	14	16.0	TT	467	18.4	1660	65.3	38	48	3750	8250	2.6	37	146	A6/30kmph	A6/20 mph
12.4-38	R1	8	11.0	TT	315	12.4	1511	59.5	32	40	1750	3850	2.7	38	127	A6/30kmph	A6/20 mph
12.4-38	R1	14	11.0	TT	315	12.4	1511	59.5	32	40	1800	3960	2.8	40	128	A6/30kmph	A6/20 mph
13.6-38	R1	8	12.0	TT	345	13.6	1565	62	36	45	1950	4290	2.0	28	131	A6/30kmph	A6/20 mph
15.5-38	R1	8	14.0	TT	395	15.5	1585	62.4	35	45	2060	4532	1.8	26	133	A6/30kmph	A6/20 mph
15.5-38	R1	14	14.0	TT	395	15.5	1585	62.4	35	45	2550	5610	3.0	43	140	A6/30kmph	A6/20 mph
16.9-38	R1	8	15.0	TT	429	16.9	1685	66.3	35	45	2575	5665	1.8	26	141	A6/30kmph	A6/20 mph
16.9-38	R1	14	15.0	TT	429	16.9	1685	66.3	35	45	3400	7480	2.3	33	151	A6/30kmph	A6/20 mph
18.4-38	R1	8	16.0	TT	467	18.4	1770	69.6	35	45	2725	5995	1.4	20	143	A6/30kmph	A6/20 mph
18.4-38	R1	14	16.0	TT	467	18.4	1770	69.6	35	45	3650	8030	2	33	153	A6/30kmph	A6/20 mph



Tractor Read Drive Wheel Tires (R-1) Deep Lug

- ◆ Specially designed for traction, these tires with deep treads, provides excellent traction for general farming.
- ◆ Self-cleaning deep lugs are especially designed to provide high traction and long life under hard working condition, including On-Road service.

SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			inch		mm	inch	mm	inch			kg	lbs	bar	psi		kmph	mph
			inch		mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
11.2-24	R1	8	10.0	TT	284	11.2	1105	43.5	28	35	1250	2750	2.5	36	116	A6/30kmph	A6/20 mph
12.4-28	R1	8	11.0	TT	315	12.4	1265	49.8	40	50	1550	3410	2.3	33	123	A6/30kmph	A6/20 mph
12.4-28	R1	12	11.0	TT	315	12.4	1265	49.8	40	50	1990	4378	3.1	44	130	A6/30kmph	A6/20 mph
13.6-28	R1	8	12.0	TT	345	13.6	1320	52.0	36	45	1650	3630	2.0	28	125	A6/30kmph	A6/20 mph
13.6-28	R1	12	12.0	TT	345	13.6	1320	52.0	36	45	2075	4565	2.4	34	133	A6/30kmph	A6/20 mph
14.9-28	R1	8	13.0	TT	378	14.9	1365	53.7	33	41	1900	4180	1.8	26	130	A6/30kmph	A6/20 mph
14.9-28	R1	12	13.0	TT	378	14.9	1365	53.7	33	41	2300	5060	2.6	37	137	A6/30kmph	A6/20 mph
16.9-28	R1	8	15.0	TT	429	16.9	1434	56.4	40	48	2180	5060	1.8	26	134	A6/30kmph	A6/20 mph
16.9-28	R1	12	15.0	TT	429	16.9	1485	58.5	36	45	2725	5995	2.4	34	143	A6/30kmph	A6/20 mph



Skid Steer tires (L2)

Special formulated tread compound provide chip & tear resistance
 Thick side wall to give protection against damage Advance tread compound for long life on paved & other hard surface. Special design for broadcast contact surface and maximum gripping power.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch		mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi	kmph
10-16.5	SKID STEER	8	8.25	TL	268	10.5	795	31.3	35	40	1370	3014	4.2	60	119	A5/25kmph	A5/16mph
10-16.5	L 2	10	8.25	TL	268	10.5	795	31.3	35	40	1560	3432	5.3	75	123	A5/25kmph	A5/16mph
12-16.5	SKID STEER	10	9.75	TL	325	12	853	33.6	35	40	1860	4049	4.5	64	129	A5/25kmph	A5/16mph
12-16.5	L 2	12	9.75	TL	325	12	853	33.6	35	40	2060	4532	5.2	74	132	A5/25kmph	A5/16mph

Heavy Duty Skid Steer & Construction Tires (L5)

Extra deep tread with sturdy lug design. Strong casing with head and cut resistant tread compound provide longer life. Extra thick side wall with rim guard gives protection against damage.,







SKID STEER TYRES L5

SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch		mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi	kmph
10-16.5	SKID STEER	12	8.25	TL	259	10.2	798	31.4	35	40	2180	4796	4.4	64	135	A5/25kmph	A5/16mph
12-16.5	SKID STEER	14	9.75	TL	307	12.1	838	33.0	35	40	2765	6083	4.8	70	144	A5/25kmph	A5/16mph

INDUSTRIAL BACKHOE LOADER TYRES-4 (MPT)

- ◆ Extra wide lugs designed to resist buckling, tearing and cracking.
- ◆ Multi step lug design provide better self-cleaning and stability.







SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar		psi	kmph
			inch		mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
12.5/80-18	MPT	12	9.0	TL	307	12.1	988	38.9	22	26	2650	5830	3.7	53	142	A8/40kmph	A8/25mph
12.5/80-18	MPT	16	9.0	TL	307	12.1	988	38.9	22	26	3150	6930	4.9	70	148	A8/40kmph	A8/25mph

Off The Road R-1 Tires

- ◆ Multi-angled and bold lug bars for service durability and self-cleaning.
- ◆ Suitably designed lug bar spacing for comfort drive & added traction.
- ◆ Strong and sturdy body plies for longer service durability.
- ◆ Tread contact patch with broader lugs for heavy duty prime-movers.



SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar		psi	kmph
			inch		mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
15.5/80-24	R1	12	13.0	TL	394	15.5	1260	49.6	32	40	2900	6380	3.0	43	145.00	A6/30kmph	A6/20mph
15.5/80-24	R1	16	13.0	TL	394	15.5	1260	49.6	32	40	3450	7590	4.1	58	151.00	A6/30kmph	A6/20mph

GRADER TIRES – G2

- ◆ Rugged sturdy tires for drive wheels of off-the-road equipment.
- ◆ Tough carcass and special trade compound with weather and ozone resistant properties to withstand cuts, snags and bruises in the most severe operation conditions.
- ◆ An open spaced traction pattern with self-cleaning property provides traction capability ideally suited for graders.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch														
13.00-24	G2	12	8.0	TL	340	13.4	1280	50.4	25	31	2725	5995	3.1	44	143	A8/40kmph	A8/25mph
13.00-24	G2	16	8.0	TL	340	13.4	1280	50.4	25	31	3250	7150	4.1	58	149	A8/40kmph	A8/25mph
14.00-24	G2	12	10.0	TL	375.0	14.7	1350	53.1	25	31	3075	6750	2.8	40	147	A8/40kmph	A8/25mph
14.00-24	G2	16	10.0	TL	375.0	14.7	1350	53.1	25	31	3650	8030	3.8	54	153	A8/40kmph	A8/25mph



GRADER TIRES – G2

- ◆ Rugged sturdy tires for drive wheels of off-the-road equipment.
- ◆ Tough carcass and special trade compound with weather and ozone resistant properties to withstand cuts, snags and bruises in the most severe operation conditions.
- ◆ An open spaced traction pattern with self-cleaning property provides traction capability ideally suited for graders.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch														
15.5-25	G2	12	12.0	TL	386	15.2	1270	50.0	24	30	2650	5840	4.0	36	147	A8/40kmph	A8/25mph
15.5-25	G2	16	12.0	TL	386	15.2	1270	50.0	24	30	6250	13750	2.8	40	153	A8/40kmph	A8/25mph

INDUSTRIAL BACKHOE LOADER TIRES R-4

- ◆ Extra wide lugs designed to resist buckling, tearing and cracking.
- ◆ Excellent tread wear and road ability, the laterally designed lugs result in even wear.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			inch		mm	inch	mm	inch			kg	lbs	bar	psi		kmph	mph
16.9-24	R-4	12	15.0	TL	450	17.7	1303	51.3	30	38	3250	7150	2.6	38	149	A8/40kmph	A8/25mph
16.9-24	R-4	16	15.0	TL	450	17.7	1303	51.3	30	38	3900	8580	3.3	48	155	A8/40kmph	A8/25mph
16.9-28	R-4	12	15.0	TL	450	17.7	1410	55.5	30	38	3550	7810	2.6	38	152	A8/40kmph	A8/25mph
16.9-28	R-4	16	15.0	TL	450	17.7	1410	55.5	30	38	3900	8580	3.3	48	155	A8/40kmph	A8/25mph



All Traction Utility Tires R-4

- ◆ Specially designed wider lugs in tread center for industrial tractor.
- ◆ Suitably planned lug spacing to control in-service buckling and cracking.
- ◆ Tougher nylon body plies for heavy duty industrial and off-the road service
- ◆ Cut and Cracks resistant tread compound for longer service life.







SIZE	PATTERN	PLY RATING	RIM WIDTH	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			inch		mm	inch	mm	inch			kg	lbs	bar	psi		kmph	mph
16.9-24	R-4	12	15.0	TL	450	17.7	1303	51.3	30	38	3250	7150	2.6	38	149	A8/40kmph	A8/25mph
16.9-24	R-4	16	15.0	TL	450	17.7	1303	51.3	30	38	3900	8580	3.3	48	155	A8/40kmph	A8/25mph
18.4-26	R-4	12	16.0	TL	475	18.7	1425	56.1	28	38	4000	8800	2.4	36	156	A8/40kmph	A8/25mph
18.4-26	R-4	12	16.0	TL	475	18.7	1425	56.1	28	38	4375	9625	2.8	41	159	A8/40kmph	A8/25mph
19.5L-24	R-4	12	17.0	TL	495	19.5	1321	52.1	28	35	3450	7590	2.0	33	151	A8/40kmph	A8/25mph
19.5L-24	R-4	16	17.0	TL	495	19.5	1321	52.1	28	35	4135	9097	3.0	44	157	A8/40kmph	A8/25mph

Compactor Tires (R-3)

- ◆ Specially designed wider lugs in tread center for industrial tractors.
- ◆ Suitably planned lug spacing to control in service buckling and cracking.
- ◆ Tougher nylon body plies for heavy duty industrial and off-the road service
- ◆ Cuts and Cracks resistant tread compound for longer service life.





SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					inch	mm	inch	mm	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch		mm	inch	mm	mm	32nds	kg	lbs	bar	psi	kmph		mph	
23.1-26	R-3	8	20.0	TL	587	23.1	1560	61.4	26	33	2900	6380	1.0	16	145	A6/30kmph	A6/20mph
23.1-26	R-3	12	20.0	TL	587	23.1	1560	61.4	26	33	3650	8030	1.7	26	153	A6/30kmph	A6/20mph
23.1-26	R-3	16	20.0	TL	587	23.1	1560	61.4	26	33	4375	9625	2.1	33	159	A6/30kmph	A6/20mph

Earthmover Tires E3-L3

- ◆ Non Directional pattern with bold lug-bars for excellent traction characteristics.
- ◆ Heavier buttress design with adequate spacing's for cooler running service.
- ◆ Strong and heavy duty NYLON body plies for higher load carrying capacity.
- ◆ Suitably designed lugs with special tread compound for extra service life.







SIZE	PATTERN	PLY RATING	RIM WIDTH  inch	TYRE	SECTION WIDTH		OVER ALL DIAMETER		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
14.00-24	E3/L3	24	10.0	TL	374	14.7	1368	53.8	25	31	9500	20900	8.6	124	186	A2/10kmph	A2/6 mph
14.00-25	E3/L3	24	10.0	TT	375	14.8	1374	54.1	25	31	9500	20900	8.6	124	186	A2/10kmph	A2/6 mph
17.5-25	E3/L3	16	14.0	TL	432	17.0	1344	52.9	28	35	7300	16060	3.0	44	158	A2/10kmph	A2/6 mph
17.5-25	E3/L3	20	14.0	TL	432	17.0	1344	52.9	28	35	8250	18150	4.0	58	164	A2/10kmph	A2/6 mph
20.5-25	E3/L3	16	17.0	TL	531	20.9	1486	58.5	31	39	8268	18190	2.7	40	167	A2/10kmph	A2/6 mph
20.5-25	E3/L3	20	17.0	TL	531	20.9	1486	58.5	31	39	9520	20944	3.2	47	170	A2/10kmph	A2/6 mph

INDUSTRIAL FORKLIFT TIRES

- ◆ Customized tread compound for cooler running & wear resistance
- ◆ Special design to meet all regular material handling applications.
- ◆ Special tread profile for improved traction & stability.







SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch														
5.00-8	Y LUG	10	3.0	TT	132	5.2	467	18.3	7	9	1415	3113	10.2	145	86	A6/30kmph	A6/20 mph
6.00-9	Y LUG	10	4.0	TT	160	6.3	540	21.2	10	13	1715	3773	8.7	124	126	A6/30kmph	A6/20mph
6.50-10	YLUG	12	5.0	TT	178	7.0	595	23.4	11	14	2180	4796	9.9	141	135	A6/30kmph	A6/20mph
7.00-12	YLUG	14	5.0	TT	180	7.1	690	27.1	12	15	2750	6050	9.2	131	143	A6/30kmph	A6/20mph
28X9-15	YLUG	14	7.0	TT	213	8.4	720	33.7	16	20	3450	7590	9.0	128	154	A6/30kmph	A6/20mph
8.15-15	YLUG	14	7.0	TT	213	8.4	720	33.7	16	20	3450	7590	9.0	128	154	A6/30kmph	A6/20mph
8.25-15	YLUG	16	6.5	TT	239	9.4	855	33.6	14	18	3550	7810	9.2	131	152	A6/30kmph	A6/20mph



Agriculture Pivot System Irrigation Tires (R-1)

- ◆ Specially designed for excellent traction & self-cleaning property for soil and paddy fields.
- ◆ Extra deep lugs provide improved performance with increased tire life.
- ◆ Natural rubber tread compound for better wear & tear resistance.
- ◆ Tough nylon casing for longer tire life.



SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYRE	SECTION WIDTH 		OVER ALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
			inch														
11.2-24	IRRIGATION	8 PR	10.0	TT	284	11.0	1105	43.5	25	30	900	1980	1.3	18	104	A6/30kmph	A6/20 mph
12.4-24	IRRIGATION	8PR	11.0	TT	315	12.4	1165	45.9	29	36	1450	3190	2.3	33	121	A6/30kmph	A6/20 mph
14.9-24	IRRIGATION	8PR	13.0	TT	378	14.9	1265	49.8	28	35	1800	3968	1.6	23	125	A6/30kmph	A6/20 mph



Nylon Three Wheeler Tires						Maximum Load	Cold Inflation Pressure	
Tire Size	Application	Ply Rating	Section Width (mm)	Over all Dia. (mm)	Non skid Depth (mm)	Single (Kgs.)	Single (PSI) (Kpa)	
4.00 -8	Auto Rickshaw	8	112	425	9	400	61	425



Nylon Three Wheeler Tires						Maximum Load	Cold Inflation Pressure	
Tire size	Application	Ply Rating	Section Width (mm)	Overall Dia. (mm)	Nons kid Depth (mm)	Single (Kgs.)	Single (PSI)	Single (Kpa)
4.00-10	Auto Rickshaw	6	110	465		437	70	425
4.50-10	Auto Rickshaw	8	125	495	10	520	80	500



Nylon Three Wheeler Tires						Maximum Load	Cold Inflation Pressure	
Tire size	Application	Ply Rating	Section Width (mm)	Overall Dia. (mm)	Non skid Depth (mm)	Single (Kgs.)	Single (PSI)	Single (Kpa)
4.50 -10	Auto Rickshaw	8	125	495	10	520	80	500



Nylon for Wheeler Tire (LCV)						Maximum Load		Cold Inflation Pressure			
Tire size	Application	Ply Rating	Section Width (mm)	Overall Dia. (mm)	Non Skid Depth (mm)	Single (Kgs.)	Dual (Kgs.)	Single (PSI)	Dual (Kpa)	Single (PSI)	Dual (Kpa)
155/80D12	ULT	8	155	556	12	560	535	65	450	65	450
165/80 D-13	ULT	8	165	597	12	670	450	—	—	—	—
165/80 D-14	ULT	8	165	620	12	575	240	—	—	—	—





Nylon for Wheeler Tires (LCV & Truck Tires)						Maximum Load		Cold Inflation pressure			
Tire size	Application	Ply Rating	Section Width(mm)	Overall Dia. (mm)	Nos kid Depth (mm)	Single	Dual	Single		Dual	
						(Kgs.)	(Kgs.)	(PSI)	(Kpa)	(PSI)	(Kpa)
6.50-14	Light Truck	8	182	705	10.5	840	795	60	425	60	425
6.50-15	Light Truck	8	175	725	11.5	875	835	62	425	62	425
6.50-15	Light Truck	10	175	725	11.5	970	920	73	500	73	500
7.00-15	Light Truck	10	205	760	11.5	1050	925	75	515	75	515
7.00-15	Light Truck	12	205	760	11.5	1175	1030	90	620	90	620
7.50-15	Light Truck	14	215	780	13	1450	1375	94	650	94	650
7.00-16	Light Truck	12	200	796	12.5	1215	1065	90	620	90	620
7.00-16	Light Truck	14	200	796	12.5	1315	1160	100	690	100	690
7.50-16	Light Truck	12	222	830	12.5	1405	1240	90	620	90	620
7.50-16	Light Truck	14	222	830	12.5	1500	1320	100	690	100	690
7.50-16	Light Truck	16	222	830	12.5	1580	1390	110	760	110	760
8.25-16	Light Truck	16	235	860	14	1845	1755	110	760	110	760
8.25-20	Truck/Bus	LUG & RIB UNDER DEVELOPMENT									
9.00-20	Truck/Bus	LUG & RIB UNDER DEVELOPMENT									
10.00-20	Truck/Bus	16	280	1065	15.5	3000	2630	115	795	105	725
10.00-20	Truck/Bus	18	280	1065	15.5	3080	2700	120	825	110	760
11.00-20	Truck/Bus	LUG & RIB UNDER DEVELOPMENT									
12.00-20	Truck/Bus	LUG & RIB UNDER DEVELOPMENT									





Nylon for Wheeler Tires (LCV)						Maximum Load		Cold Inflation			
Tire Size	Application	Ply Rating	Section Width (mm)	Overall Dia. (mm)	Non Skid Depth (mm)	Single	Dual	Single		Dual	
						(Kgs)	(Kgs)	(PSI)	(Kpa)	(PSI)	(Kpa)
7.00-15	Light Truck	12	205	770	17	1175	1030	90	620	90	620
7.50-15	Light Truck	14	220	800	15	1450	1375	94	650	94	650
7.00-16	Light Truck	14	205	807	18	1315	1160	100	690	100	690
7.50-16	Light Truck	16	220	835	17.4	1580	1390	110	760	110	760
8.25-16	Light Truck	16	230	835	17.6	1850	1750	110	760	110	760
8.25-16	Light Truck	18	230	855	17.6	1900	1800	115	795	115	795
8.25-20	Light Truck	LUG & RIV UNDER DEVELOPMENT									
9.00-20	Light Truck	LUG & RIV UNDER DEVELOPMENT									
10.00-20	Light Truck	18	285	1080	18.5	3080	2700	120	825	110	760
11.00-20	Light Truck	LUG & RIV UNDER DEVELOPMENT									
12.00-20	Light Truck	LUG & RIV UNDER DEVELOPMENT									
12.00-24	Light Truck	LUG & RIV UNDER DEVELOPMENT									



Nylon for Wheeler tires (LCV & Truck Tires)						Maximum Load		Cold Inflation Pressure			
Tire size	Application	Ply Rating	Section Width (mm)	Overall Dia. (mm)	Non skid Depth (mm)	Single	Dual	Single		Dual	
						(Kgs.)	(Kgs.)	(PSI)	(Kpa)	(PSI)	(Kpa)
10.00-20	Truck	18	285	1080	18.5	3080	2700	120	825	110	760



Earthmover Tires E3-L3Mining(Truck Tire)						Maximum Load		Cold Inflation Pressure			
Tire size	Application-on	Ply Rating	Section Width (mm)	Overall Dia. (mm)	Non skid Depth (mm)	Single	Dual	Single		Dual	
						(Kgs.)	(Kgs.)	(psi)	(Kpa)	(psi)	(Kpa.)
10.00-20 ML	Mining (Truck)	18	275	1075	22.5	2800	--	110	760	--	--
11.00-20 ML	Mining (Truck)	18	292	1117	22.5	3000	--	110	760	--	--



TWO WHEELER TYRES



90/100-10



90/100-10



90/100-10



2.75-17
2.75-18



2.75-18
2.75-17



2.75-18
2.75-17



3.75-12



3.75-12



3.75-12

TWO WHEELER TYRES



100/90-17




100/90-18



3.75-12



3.75-12



**3.00-17 2.75-18
2.75-17 3.00-18**



**80/100-17
80/100-18**



**3.00-17 2.75-18
2.75-17 3.00-18**



**90-90-12
3.00-18**



**120-80.17
100-90.17**



90-90.17



HANDAS RUBBERS PRIVATE LIMITED

**Manufactured Unit:- Opp Industrial Area, New Rohtak Road,
Bye Pass Sonipat-131001. Haryana. (India)**